

# STARGUN SOLO



## TECHNICAL FEATURES

### NEW LINE OF AFFORDABLE EXTRUDERS SOLO 20, SOLO 30, SOLO 40

- Welding quality
- Simplified electronics
- Single temperature control
- Reliability and performance
- Lightweight extruder body
- Weight balance
- 360 ° rotatable welding tip support
- "Engine block" safety system avoids cold starts
- Rotatable handle with quick release handle
- Wide range of accessories

## PLUS

- SIMPLE
- ROBUST
- RELIABLE
- BALANCED

	SOLO 20	SOLO 30	SOLO 40
Voltage	230 V	230 V	230 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Power	2700 W	2950 W	3100 W
Thermoregulator double control	✓	✓	✓
Max air output T°	360° C	360° C	360° C
Material	HDPE - PP	HDPE - PP	HDPE - PP
Rod Ø mm	3 - 4	3 - 4 - 5	4 - 5
Max output HDPE	~ 2 Kg/h rod Ø 4 mm	~ 3 Kg/h rod Ø 5 mm	~ 4 Kg/h rod Ø 5 mm
Max output PP	~ 2 Kg/h rod Ø 4 mm	~ 3 Kg/h rod Ø 5 mm	~ 3 Kg/h rod Ø 5 mm
Weight	6,85 Kg	7,1 Kg	7,6 Kg
Dimension mm	450 x 310 x 100	500 x 310 x 100	550 x 310 x 100
Conformity mark	CE	CE	CE

## FLOW



Hot gas welders.

The HD-PRO and SPHERA models integrate powerful fan to guarantee a precise hot airflow that is necessary to use the tool at its best.

The STYLO model is equipped with a temperature power regulator, very light and versatile as well, use an external compressed air supply.

All models are available in 120 V or 230 V.